

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 10-265977  
(43)Date of publication of application : 06.10.1998

(51)Int.Cl. C23F 4/00  
C23C 16/50  
H01L 21/205  
H01L 21/3065  
H05H 1/46

(21)Application number : 10-022736 (71)Applicant : TOKYO ELECTRON LTD  
(22)Date of filing : 19.01.1998 (72)Inventor : KAZAMA KOICHI  
KOIZUMI KATSUYUKI  
TAGUCHI CHIHIRO  
ONO KATSUHIKO  
SAKANO SHINJI


(30)Priority  
Priority number : 09 24312 Priority date : 23.01.1997 Priority country : JP

## (54) PLASMA PROCESSING DEVICE

## (57)Abstract:

PROBLEM TO BE SOLVED: To provide a shield ring by which an interval of cleaning or exchanging can be lengthened and further a maintenance cost can be reduced.

SOLUTION: The shield ring 140 is constituted of an inside member 142 and an outside member 144 and the inside member 142 is arranged at a position where deposit is easily stuck thereto and sputtering is easily executed. Further, the inside member 142 is formed of an insulating resin such as a polyimide series resin which is more hardly stack with deposits than the outside member 144 and is hardly sputtered and has heat resistance and sputtering resistance.



## LEGAL STATUS

[Date of request for examination] 06.08.2001  
[Date of sending the examiner's decision of rejection]  
[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]  
[Date of final disposal for application]  
[Patent number] 3424903  
[Date of registration] 02.05.2003  
[Number of appeal against examiner's decision of rejection]  
[Date of requesting appeal against examiner's decision of rejection]  
[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

BEST AVAILABLE COPY

\* NOTICES \*

JPO and NCIPi are not responsible for any damages caused by the use of this translation.


1. This document has been translated by computer. So the translation may not reflect the original precisely.

2. \*\*\*\* shows the word which can not be translated.






3. In the drawings, any words are not translated.


DRAWINGS

[Drawing 2]




[Drawing 5]






[Drawing 4]




[Drawing 7]


BEST AVAILABLE COPY



[Drawing 9]




[Drawing 6]




[Drawing 8]

BEST AVAILABLE COPY



[Drawing 10]



[Translation done.]

BEST AVAILABLE COPY